Description

A[illegible]——[illegible]

[illegible]

[illegible]38X38CM[illegible]40X50CM[illegible]

Feature

Temp
35
Time 1
25
Time 2
25
°C
COUNTER
5
OK
RESET

[illegible] [illegible] [illegible] [illegible]
[illegible]
[illegible] [illegible] [illegible]0-10[illegible]
[illegible] [illegible]
[illegible] [illegible] [illegible]
[illegible] [illegible] 15 [illegible]6 [illegible]±2~3cm[illegible]“[illegible]”[illegible]
[illegible] [illegible] p F AST [illegible] d [illegible] e H [illegible] e [illegible] [illegible]

Specification

[illegible]	[illegible]-A15 / [illegible]-A20
[illegible]	[illegible]
[illegible]	GY-08 [illegible]
[illegible]	0-10
[illegible]	230℃
[illegible]	±0.5%
[illegible]	120V / 220V[illegible]
[illegible]	50/60[illegible]
[illegible]	35.5[illegible]/43[illegible]
[illegible]	39.5[illegible] / 49.5[illegible]
[illegible]	524x390x420mm / 635x406x420mm
[illegible]	650x510x510mm / 780x540x550mm
[illegible]	CE[illegible]
[illegible]	[illegible]

Application

Microtec [illegible]T[illegible]

Gallery

Machine Warranty

Microtec [illegible]Microtec [illegible]

* [illegible]
* [illegible]
* [illegible]
* [illegible]