Description

Microtec LZP-40-DH [illegible]

[illegible]

[illegible] [illegible] [illegible]

[illegible] [illegible]

[illegible] [illegible]

[illegible] [illegible]

Feature

GY-06[illegible] [illegible]

[illegible] [illegible]

□□□□□□□□ □□□□□□□□□□□□12/20/25mm□□□□□□□

□□□□□□□□□□□□ □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

Specification

□□□	LZP-40-DH
□□□□□	□□□□□□□□□
□□□□	2×100*25CM
□□□	2× GY-06 □□□□□□□□□□
□□□	2×Ø28*195MM*140KG
□□□□□□	20□□
□□□ **200°C** □□□	32□□
□□□□	25□
□□	220V
□□	22A
□□	4.85□□
□□	50□□/60□□
□□□□	0-999 □
□□□□	225℃
□□□□□	±0.5%
□□□□	218x83x55□□
□□□□	120x95x61cm□□□□□□ 120x68x70cm□□□□□□□□
□□□	168□□100□□
□□	□□ 1 □□□□
□□□	12/20/25mm□□□□□□□□□□

LZP-40-DH

Feeding and Collecting device: Feed and collect lanyard easily, no position deviation of lanyard.

GY06 Controller: Two Individual Digital Time & Temp. Control.

Electric magnets: The upper platen will open automatically when the time count down.

Feeding Device Locating Piece suitable for: 12/20/25mm width Lanyard (downward compatibility)

Double Heat Platens: Up and base heating platens ensure two sides transfer per time.

Woollen felt: The buffer between the two heating platens,ensures the flatness of the contact surface.

PRODUCT ADVANTAGE

1 DOUBLE HEAT PLATENS:

Up and base heating platens ensure two sides transfer per time.

2 ELECTRIC MAGNETS:

The upper platen will open automatically when the time count down.

3 GY06 CONTROLLER:

Two Individual Digital Time & Temp. Control.

4 FEEDING AND COLLECTING DEVICE:

Feed and collect lanyard easily, no position deviation of lanyard.

GALLERY

APPLICATION