

Description

Microtec MTX 68 1730mm 9.8(250mm)

MTX-68 68 (1730 mm) 1730 mm 9.8(250mm)

Microtec MTX-68



Feature

Microtec MTX

MTX-68

68

9.8

MTX-68

MTX-68

MTX-44(68)

Six mandrels: 3 for feeding and 3 for take-up after sublimation.

Integrated sports tables: allows cut piece and roll-to-roll transfer applications.

Spring Loaded take-up Mandrels: No tools are required to load or remove media from the calander.

Forward & Reverse Button: if the feeding with problem, you can turn the button to REV, then the material will return safely.

Tension Handle: Easy and quick to control the tension between the blanket and oil drum ; When press it down, tension is big and blanket is tight; When press it up, blanket is separate.

Adjusting Rod: Easy to adjust the tension and position of blanket.

Take-up mandrels Speed Controller: Easy to adjust the collecting speed of take-up mandrels accordingly to the belt speed calander.

Belt Speed Controller: Easy to adjust the speed of belt.

Automatic cool down: After you turn off the "Power" and "Heat", the machine will cool down automatically (factory setting is cool down for 2 hours).

Specification

	MTX-44	MTX-68
□□□□□□	MTX-44	MTX-68
□□□□□□	44□□□ (1200mm)	68□□□ (1730mm)
□□□□□□□	Φ7.8" (200mm)	Φ9.8" (250mm)
□□□□□	392°F (200°C)	392°F (200°C)
□□□	1	3
□□□	□□□□□□□ □□	
□□□□□□	□□□□□□□□□□□□	
□□□□□□□	0□1100mm/□	0□1200mm/□
□□□□□□□	□□□□□6□□□□□3□□□□□□□3□	
□□□□□□□□□□	350mm	
□□□□□□□□□	45kg	
□□	AC220V 50HZ □□	220VAC 50HZ □□
□□	27A	30A
□	6KW	11KW

噪音值	30DB	30DB
重量	450kg/	/
尺寸	163×98×132cm	230×130×151cm
尺寸	183×120×163cm	248×145×183cm

Application

MTX 是 Microtec 的 MTX 系列，具有多种应用。Microtec 的 MTX 系列具有多种应用，包括：

应用：

- 工业应用
- 农业应用
- 农业应用
- 农业应用

NEW

CALENDER ROLL TO ROLL 44" & 68"

Affordable

Ease to use

3feed,3take-up

Dye sublimation
transfer printing

All steel component
construction



APPLICATION

