

Description

Microtec LZP-40-DH 雙面雙層加熱壓印機，採用雙面雙層加熱板，可同時在兩面進行壓印，提高生產效率。該機配備自動進料及收料裝置，操作簡便，且具備時間倒數功能，確保生產過程的精確控制。

主要特點：

• 雙面雙層加熱板：可同時在兩面進行壓印，提高生產效率。

• 自動進料及收料裝置：操作簡便，提高生產效率。

• 時間倒數功能：確保生產過程的精確控制。

• 雙面雙層加熱板：可同時在兩面進行壓印，提高生產效率。

• 自動進料及收料裝置：操作簡便，提高生產效率。



Double Heating Platens
Lanyard Heat Press Machine with Collecting Device

- Up & Base Two Heating Platens
- Two Sides Lanyard Transfer Per Time
- Easy Operation with Feeding & Collecting Device
- No Position Deviation of Lanyard
- Auto Open with Time Count Down

The image shows the Microtec LZP-40-DH lanyard heat press machine, which is a compact, industrial-grade device with a red and black frame. It features two heating platens (top and bottom) and a central mechanism for feeding and collecting lanyards. To the right of the machine, three lanyards are displayed, each with a different color (green, orange, and blue) and the text 'CHINA TEL' and 'PACIFIC' printed on them. The background is a blue and white geometric pattern.

LZP-40-DH



Feeding and Collecting device: Feed and collect lanyard easily, no position deviation of lanyard.



GY06 Controller: Two Individual Digital Time & Temp. Control.



Electric magnets:The upper platen will open automatically when the time count down.



Feeding Device Locating Piece suitable for:12/20/25mm width Lanyard (downward compatibility)



Double Heat Platens: Up and base heating platens ensure two sides transfer per time.



Woollen felt:The buffer between the two heating platens,ensures the flatness of the contact surface.

DESCRIPTION



Double Heat Platens Lanyard Heat Press Machine with Feeding Device, LZP-40-DH is new upgraded for lanyard/ribbon sublimation transfer. This lanyard heat press machine is heavy duty and equipped with up and base 2pcs of 25x100cm size heating platens, which ensure you can transfer two sides of lanyard at one time. With the electric magnets, The upper platen will open automatically when the time count down.

Also equipped with feeding and collecting device,it can feed and collect lanyard easily, no position deviation of lanyard.

LZP-40-DH Double Heat Platens Lanyard Heat Press, it can use for 12/20/25mm width Lanyard/ribbon.

This Lanyard Heat Press is an ideal choice for textile sublimation transfer.

PRODUCT ADVANTAGE



1 DOUBLE HEAT PLATENS:

Up and base heating platens ensure two sides transfer per time.

2 ELECTRIC MAGNETS:

The upper platen will open automatically when the time count down.





3 GY06 CONTROLLER:

Two Individual Digital Time & Temp. Control.

4 FEEDING AND COLLECTING DEVICE:

Feed and collect lanyard easily, no position deviation of lanyard.



SPECIFICATION

Machine Type:	Auto Open,Double Heat Platens
Heat Platen Size:	2 x 100*25CM
Controller:	2xGY-06 Digital Time & Temp. Control
Gas Spring:	2xØ28*195MM*140KG
Printable Articles: 20mm	20mm
Time Need Heating to 200°C:	32minutes
Opening Angle:	25 degree
Voltage:	220V
Current:	22A
Power:	4.85KW
Frequency:	50HZ/ 60HZ
Time Range:	0-999 Sec.
Maximum Temp:	225 C
Temperature Accuracy:	±5
Machine Size:	104.3*78.8*45.5cm
Carton Size:	120*95*61cm (wood case for machine) + 120*68*70cm (wood case for feeding device) (total 2 wood cases)
Net Weight:	90KG+80KG
Gross Weight:	138.6KG+120.0KG
Accessories :	Including 1pc of woollen felt
Feeding Device Locating Piece suitable for:	12/20/25mm width Lanyard

GALLERY



APPLICATION



GY-06 数字控制器 用于各种工业场合 精度高 稳定性好 使用寿命长 体积小 重量轻 安装方便 操作简单 维护容易 价格低廉 是工业控制领域的理想选择



Microtec LZR-40-DH: 2x100*25mm 2x GY-06 2x Ø28*195MM*140KG 20mm 32 25 220V 22A 4.85KW 50HZ/60HZ 0-999 225°C ±0.5% 219x83x55cm 120*95*61cm (不含送料) 120x68x70cm 90x80 138.6KG120.0KG 1 12/20/25mm (不含送料)



Microtec LZR-40-DH: 2x100*25mm 2x GY-06 2x Ø28*195MM*140KG 20mm 32 25 220V 22A 4.85KW 50HZ/60HZ 0-999 225°C ±0.5% 219x83x55cm 120*95*61cm (不含送料) 120x68x70cm 90x80 138.6KG120.0KG 1 12/20/25mm (不含送料)



Microtec LZR-40-DH: 2x100*25mm 2x GY-06 2x Ø28*195MM*140KG 20mm 32 25 220V 22A 4.85KW 50HZ/60HZ 0-999 225°C ±0.5% 219x83x55cm 120*95*61cm (不含送料) 120x68x70cm 90x80 138.6KG120.0KG 1 12/20/25mm (不含送料)

Specification

型號	LZR-40-DH
品牌	Microtec
規格	2x100*25mm
刀頭	2x GY-06
刀架	2x Ø28*195MM*140KG
厚度	20mm
溫度	32
速度	25
電壓	220V
電流	22A
功率	4.85KW
頻率	50HZ/60HZ
行程	0-999
溫度	225°C
精度	±0.5%
尺寸	219x83x55cm
重量	120*95*61cm (不含送料) 120x68x70cm
速度	90x80
重量	138.6KG120.0KG
行程	1
厚度	12/20/25mm (不含送料)

Application

Microtec LZR-40-DH: 2x100*25mm 2x GY-06 2x Ø28*195MM*140KG 20mm 32 25 220V 22A 4.85KW 50HZ/60HZ 0-999 225°C ±0.5% 219x83x55cm 120*95*61cm (不含送料) 120x68x70cm 90x80 138.6KG120.0KG 1 12/20/25mm (不含送料)

Machine Warranty:

Microtec 提供一年保固 Microtec 提供一年保固

* □□□□□□ □□□□□□□□□□□□□□□□□□

* 2□□□□□

* □□□□□□□□□□□ 5 □□□□□□

※□□□□□□□□5□□□□□□□□□□