Description

Microtec LZP-40-DH [illegible] 1 [illegible]

[illegible]

[illegible]: [illegible] 2 [illegible]

[illegible]: [illegible]

[illegible]: [illegible]

[illegible]: [illegible]

Feature

GY-06 [illegible] [illegible]

[illegible]: [illegible]



[illegible]: [illegible]12/20/25mm[illegible]



[illegible]: [illegible]

Specification

[illegible]	LZP-40-DH
[illegible]	[illegible]
[illegible]	2×100*25[illegible]
[illegible]	2× GY-06 [illegible]
[illegible]	2×Ø28*195MM*140KG
[illegible]	20mm
200°C[illegible]	32[illegible]
[illegible]	25[illegible]
[illegible]	220V
[illegible]	22A
[illegible]	4.85KW
[illegible]	50HZ/60HZ
[illegible]	0[illegible]999[illegible]
[illegible]	225℃
[illegible]	±0.5%
[illegible]	218×83×55cm
[illegible]	120x95x61cm ([illegible]) 120x68x70cm[illegible]
[illegible]	168KG100KG
[illegible]	[illegible]1[illegible]
[illegible]	12/20/25mm[illegible]([illegible])

LZP-40-DH

Feeding and Collecting device: Feed and collect lanyard easily, no position deviation of lanyard.

GY06 Controller: Two Individual Digital Time & Temp. Control.

Electric magnets: The upper platen will open automatically when the time count down.

Feeding Device Locating Piece suitable for: 12/20/25mm width Lanyard (downward compatibility)

Double Heat Platens: Up and base heating platens ensure two sides transfer per time.

Woollen felt: The buffer between the two heating platens,ensures the flatness of the contact surface.

PRODUCT ADVANTAGE

1 DOUBLE HEAT PLATENS:

Up and base heating platens ensure two sides transfer per time.

2 ELECTRIC MAGNETS:

The upper platen will open automatically when the time count down.

3 GY06 CONTROLLER:

Two Individual Digital Time & Temp. Control.

4 FEEDING AND COLLECTING DEVICE:

Feed and collect lanyard easily, no position deviation of lanyard.

GALLERY

APPLICATION