

Microtec MTX-68 是 Microtec 公司最新推出的一款 44 英寸和 68 英寸的卷对卷热压机。它采用全钢结构，具有高精度温度控制功能，可确保在整个转移过程中的一致性。该设备还具有耐用且易于机械调整的驱动带，无需压缩空气即可实现。此外，它还配备了数字控制器和热耦合器，以确保全年生产的稳定性。

Microtec MTX 卷对卷热压机是染料升华纸转移应用的理想选择。它提供精确的温度固定，适用于广泛的纺织应用，从而节省生产时间。其坚固的全钢结构可提供高质量的性能并确保稳定性。Microtec 卷对卷热压机是为全年生产而设计的。

44" & 68" CALENDER ROLL TO ROLL HEAT PRESS

- All steel component construction
- Temperature accuracy is controlled by thermocouple, ensuring consistency during the entire transfer process
- Durable driving belt (230°C high temperature resistant)
- Easily mechanically adjusted driving belt without the need of compressed air
- Digital controllers and heat couplings for year on year stability




DYE SUBLIMATION PAPER TRANSFER

ROLL to ROLL: calenders for printing continuous and reel-wound materials
 PIECE to ROLL: special calenders capable of operation in both modes
 (material in cut pieces and/or in rolls)

Description

Microtec MTX calenders are an affordable, easy to use solution for all your dye sublimation paper transfer applications. MTX calenders deliver precision temperature fixation to a broad range of textile applications, thus saving time on production. An all steel solid construction provides high quality performance and ensures. MTX calenders are built for year on year production.





MTX-44



MTX-68

MTX-44(68)

Six Mandrels: 3 for feeding and 3 for take-up after sublimation.

Integrated sports tables: allows cut piece and roll-to-roll transfer applications.

Spring Loaded Take-up Mandrels: No tools are required to load or remove media from the calender.

Take-up mandrels Speed Controller: Easy to adjust the collecting speed of take-up mandrels accordingly to the belt speed calender.

Belt Speed Controller: Easy to adjust the speed of belt.

Forward & Reverse Button: If the feeding with problem, you can turn the button to REV, then the material will return safely.

Tension Handle: Easy and quick to control the tension between the blanket and oil drum ; When press it down, tension is big and blanket is tight; When press it up, blanket is separate.

Adjusting Rod: Easy to adjust the tension and position of blanket.

Automatic Cool Down: After you turn off the "Power" and "Heat", the machine will cool down automatically (factory setting is cool down for 2 hours).

SPECIFICATIONS

MODEL NO.	MTX-44	MTX-68
MAX. WORKING WIDTH	44"(1200mm)	68"(1730mm)
DIA OF DRUM	Φ7.8"(200mm)	Φ9.8"(250mm)
MAX. TEMPERATURE	392°F(200°C)	392°F(200°C)
HEATING ELEMENTS	1	1
HEATING MEDIA	Thermal Oil	
CONTROLLER	Digital temperature & time control	
MAX. FEEDING SPEED	0-1100mm/min	0-1200mm/min
NUMBER OF MANDRELS INCLUDED	6 mandrels, 3 feed, 3 take-up	
MAX. MATERIAL ROLL DIMENSION	350mm	
MAX. ROLL WEIGHT	45kg	
VOLTAGE	220VAC 50HZ Single Phase	220VAC 50HZ Three Phase
CURRENT	27A	30A
POWER	6KW	11KW
NOISE LEVEL	30DB	30DB
NET/GROSS WEIGHT	450kg/	/
MACHINE SIZE	1630*976*1315mm	2300*1272*1505mm
PACKING SIZE	1830*1190*1630mm	2480*1440*1830mm

APPLICATION

01

Printed carpet

Sublimation transfer to roll carpet, rug, blanket, floor mat with brilliant colors.



02

Decorative cloth

It can be applied to curtain cloth, tablecloth, sofa cloth, and so on.

03

Fashion apparel

Sublimation printable cotton, linen, fibre, silk, and other fabrics of clothing, dress, suits, coat, accessories, etc.





04

Sportswear

Like football suit, basketball jersey, swimwear, etc.

05

Flags, banners

Transfer of flags and banners suitable for advertising industry



06

All kinds of cloth

Transfer printing of cloth of various sizes and materials, bright and saturated color, without distortion

Scan for more video details



Description

MTX 是 一种 用于 切割 各种 厚度 的 金属 板 的 设备。 MTX 具有 多种 规格， 以满足 不同的 切割 需求。 MTX 切割 速度快， 精度高， 且 易于 操作。

Feature

切割 厚度： 切割 厚度 范围 为 3 英寸。
 切割 速度： 切割 速度 为 3 英寸/分钟。
 切割 精度： 切割 精度 为 ±0.005 英寸。
 切割 噪音： 切割 噪音 为 30dB。
 切割 重量： 切割 重量 为 45kg。
 切割 电压： 切割 电压 为 220VAC 50HZ。
 切割 功率： 切割 功率 为 6KW。
 切割 噪音： 切割 噪音 为 30dB。
 切割 重量： 切割 重量 为 450kg/。

Specification

	MTX-44	MTX-68
切割 厚度	44英寸(1200mm)	68英寸(1730mm)
切割 速度	Φ7.8"(200mm)	Φ9.8"(250mm)
切割 精度	392°F(200°C)	392°F(200°C)
切割 重量	1	3
切割 噪音	30	
切割 电压	220VAC & 50HZ	
切割 功率	0~1100mm/	0~1200mm/
切割 噪音	切割 噪音 6英寸(3英寸)3	
切割 重量	350mm	
切割 电压	45kg	
切割 功率	220VAC 50HZ	220VAC 50HZ
切割 噪音	27A	30A
切割 重量	6KW	11KW
切割 精度	30DB	30DB
切割 速度	450kg/	/
切割 重量	1630×976×1315mm	2300×1272×1505mm
切割 噪音	1830×1190×1630mm	2480×1440×1830mm

Machine Warranty:

- * 切割 1 英寸
- * 切割 噪音 为 30dB

Application

切割 厚度： 切割 厚度 范围 为 3 英寸。
 ROLL to ROLL: 切割 速度 为 3 英寸/分钟。
 PIECE to ROLL: 切割 精度 为 ±0.005 英寸。

