[illegible] MTX-68 [illegible] .[illegible]

[illegible] 50% [illegible] 44 [illegible] ([illegible]) .

DYE SUBLIMATION PAPER TRANSFER

ROLL to ROLL: calenders for printing continuous and reel-wound materials
PIECE to ROLL: special calenders capable of operation in both modes
(material in cut pieces and/or in rolls)

MTX-44

MTX-68

MTX-44(68)



SPECIFICATIONS

MODEL NO.	MTX-44	MTX-68
MAX. WORKING WIDTH	44"(1200mm)	68"(1730mm)
DIA OF DRUM	Φ7.8"(200mm)	Φ9.8"(250mm)
MAX. TEMPERATURE	392°F(200℃)	392°F(200℃)
HEATING ELEMENTS	1	1
HEATING MEDIA	Thermal Oil	
CONTROLLER	Digital temperature & time control	
MAX. FEEDING SPEED	0-1100mm/min	0-1200mm/min
NUMBER OF MANDRELS INCLUDED	6 mandrels, 3 feed, 3 take-up	
MAX. MATERIAL ROLL DIMENSION	350mm	
MAX. ROLL WEIGHT	45kg	
VOLTAGE	220VAC 50HZ Single Phase	220VAC 50HZ Three Phase
CURRENT	27A	30A
POWER	6KW	11KW
NOISE LEVEL	30DB	30DB
NET/GROSS WEIGHT	450kg/	/
MACHINE SIZE	1630*976*1315mm	2300*1272*1505mm
PACKING SIZE	1830*1190*1630mm	2480*1440*1830mm

APPLICATION

01

Printed carpet

Sublimation transfer to roll carpet, rug, blanket, floor mat with brilliant colors.

02

Decorative cloth

It can be applied to curtain cloth, tablecloth, sofa cloth, and so on.

03

Fashion apparel

Sublimation printable cotton, linen, fibre, silk, and other fabrics of clothing, dress, suits, coat, accessories, etc.

04

Sportwear

Like football suit, basketball jersey, swimwear, etc.

05

Flags, banners

Transfer of flags and banners suitable for advertising industry

06

All kinds of cloth

Transfer printing of cloth of various sizes and materials, bright and saturated color, without distortion

Scan for more video details

Description

□□□□□□□ MTX □□□ MTX □□□ MTX □□□□□□□□□□□□□□□□□□□□□□□□□□

Feature

□□□□□□□□□□□□□□: □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□
6 □□□□□: □□□□□□□□□□□□□□□□□□□ 3 □
□□□□□□□□□□□□□□□□□□□: □□
□□□□□□□□□□□ □□□□□□□□□□□□□□□□□□□□□REV□□□□□□□□□□□□□□□□□□□□□□
□□□□□□□□□□□□□ □□
□□□□□: □□□□□□□□□□□□□□□□□□□□□□□□□□□□□
□□□□□□□□□□□□□□□□□□□ □□□□□□□□□□□□□□□□□
□□□□□□□□□□□ □□□□□□□□□□□□□□**:** □□
□□□□□□□□□: □□ (□□□□□□□□□□□ 2 □□□□□□□□□□□□□□□)□

Specification

□□□□□□□	MTX-44	MTX-68
□□□□□□□	44□□□□1200mm□	68□□□□1730mm□
□□□□□□□	Φ7.8"(200mm)	Φ9.8"(250mm)
□□□□□□	392℉(200℃)	392℉(200℃)
□□□	1	3
□□□□	□□	
□□□□□□□	□□□□□□□ & □□ □□	
□□□□□□□□	0□1100mm/□	0□1200mm/□
□□□□□□□□□□	□□□□□6□□□□3□□□□□□3□	
□□□□□□□□	350mm	
□□□□□□□□□	45kg	
□□	220VAC 50HZ □□	220VAC 50HZ □□
□□□□	27A	30A
□	6KW	11KW
□□□□□	30DB	30DB
□□/□□□	450kg/	/
□□□□□	1630×976×1315mm	2300×1272×1505mm
□□□□□□□□□	1830×1190×1630mm	2480×1440×1830mm

Machine Warranty:

* □□□ 1 □□□□□
* □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

Application

□□□□□□□□□□□□□:
□□
ROLL to ROLL: □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□
PIECE to ROLL: □□□□□□□□□□□□□□□□□□□□□□□□□□□□□ (□□□□□□□□□□□□/□□□□□□□□□□□□□)