□□□ □□□ □□ Microtec□ ASTM □□□ □□ □ □□□ □□□ □□□ □□ □□ □□□□ □□□□□ □□□□□. □□ □□ □□ □□□ □□□□□ □□□ ASTM □ □□□□ □ □□ □□ □□□□ □□□□ □□□□ □□□□□. [80x100cm(32"x40")](#), 100x120cm(40"x48") □ 100x160cm(40"x64"). □□ □□ □□□□ □□□□ □□ □□ □□□ □□□□□□.

Microtec ASTM □ □□□ □□□ □□□□□□□. [□□ □ □□□ □□](#), □□□ □□□ □ □□ □□□ □□□□□. ASTM □□□ □□ □ □□□ □□□□ □□ □ □□ □□□□ □□ □□ □□□ □□□ □□□ □ □□ □□□□ □□□□ □ □□□□□. [□□ XSTM □ □□□](#). □□□ ASTM□ □□□□ □□ □□□ □□□ □□, □ □□ □□, □□ □□ □□ □□ □□□ □□□ □□□□ □□□□ □□□□□.

□□□ □□ [ASTM-S □□](#), ASTM □ □□□ □□□ □□ □□ □□□□□ □□□ □□ □□ □□□ □□□□ □□□□□□.

□□□□□□□. □ □□□ □□□ □□□ □□□ □□ □□□□□. ASTM □□□□ □□□□ □□ □□□ □□ □□□ CE □□□ □□□□ □□ □□ □□□ UL □□□ □ □□□□ □□□□ □□□□ □□□ □□□ □□□□□.

Microtec ASTM □□ □ □□□□ □□□ □□ □ □ □□ □□ □□□ □□□□□ □□□□□ □□□ □□□ □□□ □□□ □□□□□.

□□□ □□ □□: □ □□ □□ □□ □□□ □□□□□ - [80x100cm(32"x40"),](#) [100x120cm(40"x48")](#)□ 100x160cm(40"x64") - □□□ □□ □□ □□□ □□.

□□ □□□: □□□ □□□ □□□ □□ □□ □□□ □□ □ □□ □□ □□□□ □□□□□.

□□ □□: □ □ □□□ □□□ □□□□ □□□ □□□ □□ □□ □□□□ □□□□ □□□ □ □□ □□□ □□□□□.

□□ □□□: □, □□, □□□ □□, □□ □□□□ □□ □□□ □□□ □□□ □□□□ □□□□ □ □□□□□□.

□□ □□□: □□ □□□ □□ □□□ □□□ □□□ □ □□□ □□ □□□□ □□□□ □□ □□□ □□□□□□.

□□□ □□: □□□ □□□ □□ □□□□ □□□ □□□ □□ □□□ □□□□□.

□□ □□□: □□□□ □□□□ □□□□ □□□□ □□ □□□ □□ □□□ □□ □ □□□ □□ □ □□□□□.

GY-06 디지털 컨트롤러: 압력과 온도를 모두 제어하고 정밀한 및 편리 제어를 보장하는 컨트롤 장치입니다. 정밀한 온도와 압력을 보장하여 인쇄물의 품질과 내구성을 최적화하기 위함입니다.

□□ 전체 슬라이드: □ 제품 넓은 슬라이드에서 적재하고 □ 같은 위치 쉽게 언로드할 적재를 배출할 수있는 것 같습니다. □ 기능은 □ 효율성 향상 시켜줍니다.

□ 개의 실린더가 있는 공기압 및 구동식: 압력 조절이 용이하여 모든 공간에, 균일한 압력으로 사용하여 설계 시스템입니다로 사용됩니다□.

공기 필터와 조절: 시스템 내에서 공기의 압력 안정 보장을 위해 공기와 □ 조절하고 여과하기 위해서 설계되어 있어 더 정확한 압력을 □ 보장하면서 □ 수 있습니다.

컨트롤 박스: 이 박스는 시스템에서 제어하는 역할을 처리하고 전체 프로세스를 안전하고 쉽게 작동하는 역할을 담당하고 있습니다.

인쇄물 제작에 있어 Microtec ASTM 기기 및 설계는 정확한 온도 및 압 편의 기능 제어 등을 제공하여 효율성을 향상시키며 품질을 보장하고 공간 사용을 최적화 할수 있습니다.

제품 모델.	ASTM-40/ ASTM-48/ ASTM-64
압력 방식	수동, 공기 방식으로
작업 크기	32"x40"/40"x48"/40"x64"(80x100cm/100x120cm/100x160cm)
온도 제어	GY-06 디지털 온도 및 압력. 제어
상부 플래튼 두께	두께 20mm 이상
하부 플래튼 두께	□
전압	220V 단상/ 220V 3상/ 380V 3상
□	5.1KW/ 7.5KW/ 9KW
시간 제어	0~999초
최대 온도	225℃
온도 안정성	±0.5%
압력	8kg/cm
기계 크기	168x138x176/ 188x157x177/ 227x156x176cm
순중량	425kg/536kg/641kg
총 중량	604kg/ 764kg/ 900kg (나무 상자로)
□	디지털식 제어, 실린더 공기 2개, 공기 압축기 옵션으로 공기 펌프는(3HP)이 포함되어 있습니다.

Pneumatic Large Format Dual-Station Heat Transfer Machine

Heat Platen Size: *80x100cm, 100x120cm, 100x160cm*

The ASTM series is high performance large format pneumatic heat presses system with significant working space for transferring high quality images onto a variety of substrates with ease. The ASTM combines a heavy-duty industrial grade solid steel frame with precise and easy to use electronics providing the best possible features for a variety of heat transfer applications.

Click the Video to Learn More

Application:

Transfer high quality images onto a variety of media - any size! Ideal for printing on t-shirts, apparel and harder to print sizes.

More

Ask for details

Features:

- 80x100cm, 100x120cm, 100x160cm Available
- Automatic Air Operated Pressing
- Double Location Design for Saving Working Time
- Integrated Tube Technology for Even Distributed Heating
- Digital Time & Temperature Controls
- Easy Shuttle Operation
- Laser-quality Iron framework
- Voltage:220V 1phase/ 220V 3phase/ 380V 3phase

More Choice:

Pneumatic Large Format Draw-out Heat Press
Item No.: APHD-40
Heat Platen Size: *75x105cm*

Pneumatic High Pressure Draw-out Heat Press
Item No.: APD-20/24
Heat Platen Size: *40x50/40x60cm*

Pneumatic Double Location Shuttle Heat Press
Item No.: APDS-15/20
Heat Platen Size: *38x38/40x50cm*

Semi-automatic Manual Large Heat Press
Item No.: STM
Heat Platen Size: *60x80cm, 80x100cm, 100x120cm, 100x140cm*

ASTM 인증 및 대량의 스포츠 의류, 광고배너, 대형의 사진 및 포스, 경질의 표면 전사, 홈패션 섬유류 및 의류의 장식 전사까지 폭넓게 사용 가능한 제품입니다.

Application>
·Sports goods.
·Advertising, flags, banners, accessories.
·Large photos, posters.
·Transfer on Hard Substrate (ceramic, aluminium, plastic, wood...)
·Textile : home finishing, apparel, curtains...