





#### DESCRIPTION



Pneumatic Double Station Shuttle Heat Press with Floor Stand & Infrared Positioning Device, STS-20 is new upgraded for t-shirt heat transfer & sublimation transfer. This machine is a shuttle type pneumatic two-station heat transfer printing machine, equipped with 2pcs of 40x50cm baseplates. Pneumatic drive, easy to operate, save time & effort, anyone can easily operate.

The dual station design also improves production efficiency. The machine is designed with a floor stand and four universal wheels, it can move around and stop anywhere you want.

It is equipped with 2 infrared cross positioning devices to help the pattern positioning and reduce the offset between the actual distance and the ideal distance.

#### **PRODUCT ADVANTAGE**



This machine is a shuttle type pneumatic two-station heat transfer printing machine, equipped with 2pcs of 40x50cm baseplates. Pneumatic drive, easy to operate, save time & effort, anyone can easily operate. The dual station design also improves production efficiency.

The machine is designed with a floor stand and four universal wheels: it can move around and stop anywhere you want.

The floor stand of the machine is designed with an upper and lower adjustment space of 0-20cm, and the working table can be raised by another 10 or 20cm.





It is equipped with 2 infrared cross positioning devices: to help the pattern positioning and reduce the offset between the actual distance and the ideal distance.

## CARRY 2 PALLETS

(pallets can be put away) : place transfer materials or common tools



## **SPECIFICATION**

Machine Type:	Pneumatic, Double Station, Infrared Positioning
Platen Size:	16"*20"/(40*50cm)
Under Plate:	Exchangeable
Machine Feet:	with floor stand & 4 universal wheels
Accessories:	with 2 pallets,2 infrared cross positioning devices
Working Mode:	Single or double hands operation(Toggle switch)
Platen Cover:	Anti – scalding cover
Controller:	GY-06 Digital Time & Temp. Control
Printable Articles:	Up to 50mm Thickness
Air Compressor Required:	Yes,1~3HP
Voltage:	110V/ 220V
Power:	1.6KW/ 1.8KW
Current:	15/20A
Frequency:	50-60HZ
Time Range:	0-999 sec.
Maximum Temp:	225 C
Temperature Accuracy:	±5%
Machine Size:	108*86*150cm
Packing Size:	115*114*164cm
Net./Gross Weight:	295/395kg(Wooden Package)

### **GALLERY**













# APPLICATION



#### Scan for more details





#### Feature



**GY-06** 00 000 000 0000 : 0 00000 0 0000 00 0000 0000. 000 00 0 000 0







**2** 00 0000 000000 (0000 00 0 0000) : 00 00 00 00 00



00 00 : 00 00 000 00 000 000 000 00 000 000 000 000 000 000.

#### Machine Warranty:

- \* 00 0 000 0000 00 00 00.
- \* 2 🛮 🖺
- \* 00 0 000 00 5 0 00.
- \* 0000 5 0 00.
- \* 0, 0000 0 00 000 00 6 00 00



















