

FULLY AUTO

Dual Station Heat Press

XPDS-20B

XPDS -20B □□ □□ □□ □□□□ □□ □□□□

□□ □ □□□□ □ **16 □□ × 20 " (40 × 50cm)** □□ □

0000 **XPDS -20B** 0 0 00 0000 0000 0000 00 000000 0 00 00 00 0000 00 0000 00000000. 0000 **16 " × 20 " Platen**, 0000 00, 00 0 000 0000 00 0 000 000000 000 00 0000 000000. 000, 00 0000 0 00 00 000 00 000000 0000 0000 0000, 00 0 000 000 000000.

11 11

- **ᐅᐃ ᐅ ᐅᐅᐅ ᐅᐅ ᐅᐅ ᐅ - ᐅᐅ ᐅᐅ ᐅᐅᐅ ᐅᐅ 2 ᐅᐅ ᐅᐅ ᐅᐅ ᐅᐅ ᐅᐅ ᐅᐅᐅᐅᐅ ᐅᐅᐅ ᐅᐅ ᐅᐅᐅ ᐅᐅᐅᐅᐅ.**
- **ᐅᐅ ᐅᐅ ᐅ ᐅᐅ ᐅᐅ - ᐅᐅ ᐅᐅᐅ ᐅᐅ ᐅᐅ ᐅᐅᐅ ᐅᐅ ᐅᐅᐅᐅᐅ ᐅᐅ ᐅᐅ ᐅᐅᐅ ᐅᐅᐅᐅᐅ.**
- **ᐅᐅ - ᐅᐅ ᐅᐅ -ᐅᐅ ᐅᐅᐅᐅ ᐅᐅᐅᐅ ᐅᐅ ᐅᐅᐅ ᐅᐅᐅᐅ ᐅᐅᐅ ᐅᐅᐅ ᐅᐅᐅ ᐅᐅ ᐅᐅᐅᐅ ᐅᐅᐅ ᐅᐅᐅᐅᐅ.**
- **ᐅᐅᐅ ᐅᐅ -ᐅᐅ ᐅᐅ ᐅᐅ ᐅᐅᐅᐅ ᐅᐅ ᐅ ᐅᐅ ᐅᐅ ᐅᐅ ᐅᐅᐅ ᐅᐅᐅᐅ ᐅᐅᐅᐅ ᐅᐅ ᐅᐅᐅ ᐅᐅᐅᐅᐅ.**
- **ᐅᐅᐅ ᐅᐅ - ᐅᐅ ᐅᐅᐅ ᐅᐅᐅᐅ ᐅᐅᐅᐅ ᐅᐅᐅᐅ ᐅᐅᐅ ᐅᐅᐅ ᐅᐅᐅᐅ ᐅᐅᐅ ᐅᐅᐅᐅ ᐅᐅᐅᐅ.**
- **ᐅᐅ ᐅᐅᐅ ᐅᐅᐅ ᐅᐅ ᐅᐅᐅ - ᐅᐅ ᐅᐅᐅ ᐅᐅ ᐅᐅ ᐅᐅ ᐅ ᐅᐅ ᐅᐅ ᐅᐅᐅ ᐅᐅᐅ ᐅ ᐅᐅᐅ ᐅᐅᐅ ᐅᐅ ᐅᐅᐅ ᐅᐅᐅ ᐅᐅᐅᐅᐅᐅ.**
- **ᐅᐅ ᐅᐅᐅ ᐅᐅᐅᐅ - 3 ᐅᐅ ᐅᐅᐅᐅᐅ ᐅᐅᐅ ᐅᐅ ᐅᐅᐅᐅᐅ GY -13 ᐅᐅᐅᐅ ᐅᐅ, ᐅᐅ ᐅ ᐅᐅᐅ ᐅᐅ ᐅᐅᐅ ᐅᐅᐅᐅᐅᐅ.**
- **ᐅᐅᐅᐅ ᐅᐅ ᐅᐅ - ᐅᐅᐅ ᐅᐅ (T- ᐅᐅ, ᐅᐅ, ᐅᐅᐅ) ᐅ ᐅᐅ ᐅᐅᐅ ᐅᐅᐅᐅ ᐅᐅᐅ ᐅᐅ ᐅᐅᐅᐅᐅ ᐅᐅᐅᐅᐅᐅᐅ.**

PRODUCT HIGHLIGHTS



Manual & Auto Mode Streamline Printing



Power-off Protection Safety Lock Mechanism



Built-in Sensor Hand-injury Prevention



Precise Alignment Effortless Operation

16 " × 20 " XPDS -20B □ □ □ □ □ □ □ □ □ □ ?

[illegible]

- 20 T- 20 0 000 00
- 00000 0 00 0 00
- 00 00 0 00 00
- 00 0000 000 0000 00 0000

100 101

[illegible]