

Description



M
MICROTEC

AUTOMATIC FEEDING DEVICE FOR LANYARD HEAT PRESS

MODEL: OMA

- Designed to work with Lanyard Heat Press
- Adjustable Winding Speed
- Enhanced Efficiency

NEW PRODUCT

Introducing our latest innovation, the Electric Lanyard/Ribbon Feeding Device, specially designed to complement our best-selling LZP-40/LZP-40DH Single/ Double-Sided Lanyard Heat Press Machine. This cutting-edge device is engineered for customers who seek efficiency and precision in their lanyard heat transfer process.

With the Electric Lanyard/Ribbon Feeding Device, you can significantly streamline your operations. After completing the heat transfer process, this device swiftly winds the ribbon, allowing you to quickly prepare for the next transfer, saving you valuable time and effort. The feeding speed is fully adjustable, empowering you to set the pace according to your specific needs, ensuring smooth and consistent results every time.

Feature

The main features of the Electric Lanyard/Ribbon Feeding Device:

Seamless Integration

Designed to work perfectly with Microtec LZP-40/LZP-40-HD Single/Double-Sided Lanyard Heat Press Machine. Our Automatic Feeding Device integrates effortlessly with your existing setup, allowing for both manual and automated production, offering you flexibility and control.

Adjustable Feeding Speed

Allows users to customize the feeding speed according to their specific needs for optimal control.

Enhanced Efficiency

Streamlines the post-transfer process by quickly feeding lanyards, reducing downtime between transfers.

Manual and Automatic Options

Switch between manual and automatic feeding modes with ease using the intuitive control panel.

User-Friendly Operation

Simple controls make it easy to operate, even for those new to heat press machines.

Versatile Compatibility

Can handle various lanyard widths and types, making it suitable for a wide range of applications.

Improved Productivity

By automating the lanyard feeding process, it helps businesses increase output and efficiency.

Durable Construction

Built with high-quality materials to ensure long-lasting performance and reliability.



Specification	
Model No.	LZP-40+ODA
Machine Type	Auto Open, With Automatic Feeding Device
Controller	GY-06 Digital Time & Temp. Control
Platen Size	100x25cm
Printable Articles	Up to 20mm Thickness
Maximum Temp.	225°C
Power	2.2KW/ 2.4KW
Voltage	110V/ 220V
Frequency	50/ 60HZ
Net Weight	
Gross Weight	
Carton Size	
Certification	CE Approval
Warranty	2 Years For Entire Machine

Application By integrating the Electric Lanyard/Ribbon Feeding Device with your LZP-40/LZP-40-HD Heat Press Machine, you'll enhance productivity, reduce downtime, and achieve a higher level of operational efficiency. This combination is perfect for businesses looking to scale up their production without compromising on quality.

